

Package: mcmsupply (via r-universe)

September 18, 2026

Type Package

Title Estimating Public and Private Sector Contraceptive Market Supply Shares

Version 1.0.3

Description Family Planning programs and initiatives typically use nationally representative surveys to estimate key indicators of a country's family planning progress. However, in recent years, routinely collected family planning services data (Service Statistics) have been used as a supplementary data source to bridge gaps in the surveys. The use of service statistics comes with the caveat that adjustments need to be made for missing private sector contributions to the contraceptive method supply chain. Evaluating the supply source of modern contraceptives often relies on Demographic Health Surveys (DHS), where many countries do not have recent data beyond 2015/16. Fortunately, in the absence of recent surveys we can rely on statistical model-based estimates and projections to fill the knowledge gap. We present a Bayesian, hierarchical, penalized-spline model with multivariate-normal spline coefficients, to account for across method correlations, to produce country-specific, annual estimates for the proportion of modern contraceptive methods coming from the public and private sectors. This package provides a quick and convenient way for users to access the DHS modern contraceptive supply share data at national and subnational administration levels, estimate, evaluate and plot annual estimates with uncertainty for a sample of low- and middle-income countries. Methods for the estimation of method supply shares at the national level are described in Comiskey, Alkema, Cahill (2022) [<doi:10.48550/arXiv.2212.03844>](https://doi.org/10.48550/arXiv.2212.03844) .

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0)

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Imports haven, purrr, rvest, survey, openxlsx, R2jags, magrittr,
foreach, tidyverse, tidybayes, runjags, rjags, rlang, abind,
dplyr, ggplot2, plyr, readxl, stringr, tibble, tidyr

URL <https://hannahcomiskey.github.io/mcmsupply/>,
<https://github.com/hannahcomiskey/mcmsupply>

Config/pak/sysreqs cmake libfontconfig1-dev libfreetype6-dev libfribidi-dev make libharfbuzz-
dev jags libicu-dev libjpeg-dev libpng-dev libtiff-dev libuv1-dev libwebp-dev libxml2-dev libssl-
dev libx11-dev zlib1g-dev

Repository <https://hannahcomiskey.r-universe.dev>

Date/Publication 2026-03-22 21:56:19 UTC

RemoteUrl <https://github.com/hannahcomiskey/mcmsupply>

RemoteRef HEAD

RemoteSha a6f30a0a04b52b780a86d6a973738df1a1e00647

Contents

calculate_SE_data_from_DTA	3
check_data_freshness	4
Country_and_area_classification	5
country_names	6
DEFT_DHS_database	6
get_data	7
get_posterior_P_samps	8
get_subnational_modelinputs	8
harvest_dhs	9
national_estimated_correlations_bivarlogitnormal	10
national_FPsource_data	11
national_FPsource_format	12
national_FPsource_VARCOV_bivarlogitnormal	12
national_inv_sigma_delta_hat_bivarlogitnorm	13
national_tau_alpha_cms_hat_bivarlogitnorm	14
national_theta_rms_hat_bivarlogitnorm	14
national_varcov_order_bivarlogitnormal	15
plot_estimates	15
pull_estimates	16
run_jags_model	17
subnat_FPsource_data	18
subnat_FPsource_format	19

<i>calculate_SE_data_from_DTA</i>	3
subnational_alpha_cms_hat	19
subnational_estimated_correlations	20
subnational_inv.sigma_delta_hat	20
subnational_tau_alpha_pms_hat	21

Index 22

calculate_SE_data_from_DTA	
<i>Calculate Standard Errors and Variance-Covariance Matrices for DHS Subnational Estimates</i>	

Description

This function reads a DHS dataset, constructs a survey design object, computes weighted estimates of modern contraceptive method sources by sector category, and exports both the proportion matrix and the variance-covariance matrix to Excel files.

Usage

```
calculate_SE_data_from_DTA(filepath, myresultsfolder)
```

Arguments

filepath	Character string. The path to the DHS .dta file.
myresultsfolder	Character string. Path to a folder where Excel outputs will be saved. The function will create the required subfolders (proportions/ and varcov/) if they do not exist.

Details

- The function:
1. Reads DHS survey microdata.
 2. Constructs derived variables such as modern method, sector, and method source.
 3. Builds a survey design using **survey**.
 4. Computes weighted proportions using `svyby()`.
 5. Extracts the associated variance–covariance matrix.
 6. Exports both datasets as Excel workbooks.

Value

A list with two elements (returned invisibly):

prop_mat Data frame of weighted estimates with counts

vcov_matrix Variance–covariance matrix tibble

Output files are written to disk as a side effect.

Examples

```
## Not run:
calculate_SE_data("data/country.dta", "results/")

## End(Not run)
```

check_data_freshness *Check Data Freshness Against DHS Reference*

Description

Compares local dataset against DHS reference data to determine if newer surveys are available or exist but are not yet publicly available.

Usage

```
check_data_freshness(
  local = NULL,
  reference = NULL,
  survey_column = "Survey Datasets",
  data_available_value = "Data Available"
)
```

Arguments

local	Data frame. Local dataset containing Country and Year columns. If NULL, uses national_FPsource_data from the mcmsupply package. Default is NULL.
reference	Data frame. Reference dataset containing Country, Year, and survey status columns. If NULL, calls harvest_dhs() to retrieve current DHS data. Default is NULL.
survey_column	Character string. Name of the column in reference data indicating survey dataset availability. Default is 'Survey Datasets'.
data_available_value	Character string. Value in survey_column that indicates data is publicly available. Default is 'Data Available'.

Value

A data frame with columns Country, Year.package, Year.most_recent, Year.most_recent_available, and Status. Status indicates whether the local data is 'Up To Date', 'More Recent Available' (publicly available), or 'More Recent Exists' (exists but not yet publicly available).

Examples

```
## Not run:
freshness <- check_data_freshness()

## End(Not run)
```

Country_and_area_classification

The Country and area classification according to the United Nations Statistical Division, Standard country or area codes for statistical use (M49). Adapted for use in FP2030 by the Track20 project. A subset of data from the United Nations country classifications

Description

The Country and area classification according to the United Nations Statistical Division, Standard country or area codes for statistical use (M49). Adapted for use in FP2030 by the Track20 project. A subset of data from the United Nations country classifications

Usage

```
Country_and_area_classification
```

Format

A data frame with 231 rows and 8 columns:

Country or area Country name

ISO Code 1, 2 & 3 number ISO country codes

Major area Continent

Region Sub-continent

Developed region Binary indicator for development status

Least developed country Binary indicator for least developed status

Sub-Saharan Africa Binary indicator for whether country is in Sub-Saharan Africa

FP2020 Binary indicator for FP2020 participation status

Source

<https://unstats.un.org/unsd/methodology/m49/>

country_names	<i>The names of the countries with national and subnational administration level data stored</i>
---------------	--

Description

The names of the countries with national and subnational administration level data stored

Usage

country_names

Format

A data frame with 30 rows and 3 columns:

Country names Country name

National level data available Indicator for whether data at the national administration level is available in the package

Subnational level data available Indicator for whether data at the subnational administration level is available in the package

DEFT_DHS_database	<i>DEFT_DHS_database A database of the design effects for some of the DHS surveys in the national and subnational datasets. Due to due to multistage and clustering of the DHS sample, the average standard error is increased by a design effect (DEFT) factor over that in an equivalent simple random sample.</i>
-------------------	--

Description

DEFT_DHS_database A database of the design effects for some of the DHS surveys in the national and subnational datasets. Due to due to multistage and clustering of the DHS sample, the average standard error is increased by a design effect (DEFT) factor over that in an equivalent simple random sample.

Usage

DEFT_DHS_database

Format

A dataframe of Country names, survey year and design effects for DHS surveys

Source

DHS final reports Appendix B, 'ESTIMATES OF SAMPLING ERRORS'.

get_data	<i>Wrapper function that retrieves the DHS data used for modelling the proportion of modern contraceptives supplied by the public and private sectors at the national and subnational administration levels.</i>
----------	--

Description

Wrapper function that retrieves the DHS data used for modelling the proportion of modern contraceptives supplied by the public and private sectors at the national and subnational administration levels.

Usage

```
get_data(
  national = TRUE,
  local = FALSE,
  mycountry = NULL,
  fp2030 = TRUE,
  surveydata_filepath = NULL
)
```

Arguments

national	TRUE/FALSE. Default is TRUE for national administration level data. FALSE retrieves subnational level data.
local	TRUE/FALSE. Default is FALSE for global runs. Decides if this is a single-country or global run.
mycountry	The name of country of interest. Default is NULL. For the names of potential countries, review vigentte .
fp2030	Default is TRUE. Filter raw data to only include the Family Planning 2030 focus countries discussed in the Comiskey et al. paper .
surveydata_filepath	Path to survey data. Default is NULL. Survey data should be a .xlsx with the following format national_FPsource_data .

Value

returns a list containing the DHS data set used for inputs into the model and the arguments that specify the data set up.

Examples

```
raw_data <- get_data(national=FALSE, local=TRUE, mycountry="Nepal")
```

`get_posterior_P_samps` *Function to pull the complete posterior sample for the national method-supply share estimates. Functionality for the subnational models is still under development.*

Description

Function to pull the complete posterior sample for the national method-supply share estimates. Functionality for the subnational models is still under development.

Usage

```
get_posterior_P_samps(jagsdata, model_output, nposterior)
```

Arguments

<code>jagsdata</code>	The inputs for the JAGS model
<code>model_output</code>	The output of the <code>mcmsupply::run_jags_model()</code> function.
<code>nposterior</code>	The number of posterior samples you wish to pull.

Value

A dataframe containing the posterior samples of national method-supply share estimates.

Examples

```
## Not run:
raw_data <- get_data(national=TRUE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2025.5, nsegments=12, raw_data)
mod <- run_jags_model(jagsdata = jagsdata, jagsparams = NULL, n_iter = 5, n_burnin = 1, n_thin = 1)
post_samps <- get_posterior_P_samps(jagsdata = jagsdata, model_output = mod, nposterior=4)

## End(Not run)
```

`get_subnational_modelinputs`
Get JAGS model inputs

Description

Get JAGS model inputs

Usage

```
get_modelinputs(startyear = 1990, endyear = 2030.5, nsegments = 12, raw_data)
```

Arguments

startyear	The year you wish to begin your predictions from. Default is 1990.
endyear	The year you wish to finish your predictions. Default is 2030.5.
nsegments	The number of knots you wish to use in your basis functions. Default is 12.
raw_data	The list of arguments and family planning source data from the 'get_data' function.

Value

A list of modelling inputs for the JAGS model.

1. Tstar is the year index for the most recent survey in each province.
2. Kstar is the knot index that aligns with Tstar.
3. B.ik are the basis functions.
4. n_years are total number of years
5. n_obs are the total number of observations
6. K are the number of knots.
7. H is K-1. Used in the calculation of first order differences of spline coefficients.
8. P_count is the number of subnational provinces/regions.
9. M_count is the number of modern contraceptive methods.
10. matchsubnat is the subnational province indexing to match the observed data to the predictions.
11. matchcountry is the country indexing to match the observed data to the predictions.
12. matchmethod is the method indexing to match the observed data to the predictions.
13. matchyears is the year indexing to match the observed data to the predictions.

Examples

```
raw_data <- get_data(national=FALSE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2030.5, nsegments=12, raw_data)
```

harvest_dhs

Harvest DHS Dataset Availability

Description

Scrapes the DHS Program website to retrieve information about the newest available datasets.

Usage

```
harvest_dhs(
  url = "https://dhsprogram.com/data/available-datasets.cfm",
  survey_column = "Survey",
  standard_dhs = TRUE
)
```

Arguments

url	Character string. URL of the DHS available datasets page. Default is "https://dhsprogram.com/data/available-datasets.cfm".
survey_column	Character string. Name of the column containing survey information. Default is 'Survey'.
standard_dhs	Logical. If TRUE, filters results to include only Standard DHS surveys. Default is TRUE.

Value

A tibble containing all tables from the DHS program URL, with added Country and Year columns extracted from the survey column.

Examples

```
## Not run:
dhs_data <- harvest_dhs()

## End(Not run)
```

national_estimated_correlations_bivarlogitnormal

The estimated national-level correlations between the rates of change in methods

Description

The estimated national-level correlations between the rates of change in methods

Usage

```
national_estimated_correlations_bivarlogitnormal
```

Format

A array of 2 matrices with 5 rows and 5 columns:

row Contraceptive method the correlation estimate refers to

column Contraceptive method the correlation estimate refers to

public_cor The estimated correlation between the rates of change in methods supplied by the public sector

private_cor The estimated correlation between the rates of change in methods supplied by the private sector

national_FPsource_data

DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Description

DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Usage

national_FPsource_data

Format

national_FPsource_data:

A data frame with 562 rows and 15 columns:

Country Country names

Method Contraceptive method name

average_year Average year of the survey

year Year of the survey

country_code ISO country codes

Public Proportion supplied by the Public sector

se.Public Standard error of proportion supplied by the Public sector

Public_n Sample size used to calculate proportion supplied by the Public sector

Commercial_medical Proportion supplied by the private Commercial medical sector

se.Commercial_medical Standard error of proportion supplied by the private Commercial medical sector

Commercial_medical_n Sample size used to calculate proportion supplied by the private Commercial medical sector

Other Proportion supplied by the private Other sector

se.Other Standard error of proportion supplied by the private Other sector

Other_n Sample size used to calculate proportion supplied by the private Other sector

check_sum Check to see if proportions sum to 1

Source

On request from DHS microdata - using the womens individuals recode file. Contact details found at https://dhsprogram.com/data/dataset_admin/login_main.cfm

national_FPsource_format

A checklist for ensuring national-level custom data is appropriate to be used for estimation

Description

A checklist for ensuring national-level custom data is appropriate to be used for estimation

Usage

national_FPsource_format

Format

A list of requirements for custom data to meet before being accepted into the model

Country Country name variable classification

Method Method name variable classification

average_year average_year variable classification

sector_category sector_category name variable classification

proportion proportion variable classification

SE.proportion SE.proportion variable classification

n n variable classification

national_FPsource_VARCOV_bivarlogitnormal

An array of variance-covariance matrices transformed onto the logit-scale via the delta method. Each matrix corresponds to the DHS survey logit-transformed observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Description

An array of variance-covariance matrices transformed onto the logit-scale via the delta method. Each matrix corresponds to the DHS survey logit-transformed observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Usage

```
national_FPsource_VARCOV_bivarlogitnormal
```

Format

```
national_FPsource_VARCOV_bivarlogitnormal:
```

An array of 2x2 matrices for each of the 608 observations in the national_FPsource_data. Each 2x2 array corresponds to the variance of the public and private sectors on the diagonal and their corresponding covariances on the off-diagonal.

Source

The variance-covariance matrices are calculated using the survey R package: `prop_mat <- svyby(~I(sector_categories), ~I(modern_method_source), design=d.s, svymean, covmat=TRUE) vcov_matrix <- vcov(prop_mat)` function.

```
national_inv_sigma_delta_hat_bivarlogitnorm
```

The median estimate for the national-level variance-covariance matrix of the delta.k terms in the multi-country national model.

Description

The median estimate for the national-level variance-covariance matrix of the delta.k terms in the multi-country national model.

Usage

```
national_inv_sigma_delta_hat_bivarlogitnorm
```

Format

A array of 2 matrices with 5 rows and 5 columns:

Array 1 Estimated public sector variance-covariance matrix

Array 2 Estimated private sector variance-covariance matrix

national_tau_alpha_cms_hat_bivarlogitnorm

The median estimates of the precision for the national-level country, sector-, method-specific intercepts in the multi-country national model. This vector is used to inform the precision in the Normal prior of the national-level intercept in single-country national models.

Description

The median estimates of the precision for the national-level country, sector-, method-specific intercepts in the multi-country national model. This vector is used to inform the precision in the Normal prior of the national-level intercept in single-country national models.

Usage

national_tau_alpha_cms_hat_bivarlogitnorm

Format

A vector of two precision estimates

national_theta_rms_hat_bivarlogitnorm

The median estimates of the national-level sub-continental, sector-, method-specific intercepts in the multi-country national model. This array is used to inform the Normal prior of the country-level intercept in the single-country national model.

Description

The median estimates of the national-level sub-continental, sector-, method-specific intercepts in the multi-country national model. This array is used to inform the Normal prior of the country-level intercept in the single-country national model.

Usage

national_theta_rms_hat_bivarlogitnorm

Format

A array of 6 matrices with 2 rows and 5 columns

national_varcov_order_bivarlogitnormal

The order of observations to join the variance-covariance array data and the DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Description

The order of observations to join the variance-covariance array data and the DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the national level

Usage

national_varcov_order_bivarlogitnormal

Format

national_varcov_order_bivarlogitnormal:

A data frame with 558 rows and 3 columns:

Country Country names

average_year Average year of the survey

Method Contraceptive method name

Source

On request from DHS microdata - using the womens individuals recode file. Contact details found at https://dhsprogram.com/data/dataset_admin/login_main.cfm

plot_estimates	<i>Wrapper function to plot the JAGS estimates</i>
----------------	--

Description

Wrapper function to plot the JAGS estimates

Usage

plot_estimates(jagsdata, model_output)

Arguments

jagsdata Output of the mcmsupply::get_modelinputs() function.

model_output The output of the mcmsupply::run_jags_model() function.

Value

A list of ggplot objects.

Examples

```
## Not run:
raw_data <- get_data(national=TRUE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2030.5, nsegments=12, raw_data)
mod <- run_jags_model(jagsdata, n_iter=5, n_burnin=1, n_thin=1)
plots <- plot_estimates(jagsdata = jagsdata, model_output = mod)

## End(Not run)
```

pull_estimates	<i>Function to pull method-supply share median estimates and credible intervals for a given year and country.</i>
----------------	---

Description

Function to pull method-supply share median estimates and credible intervals for a given year and country.

Usage

```
pull_estimates(model_output, year, country)
```

Arguments

model_output	The output of the mcmsupply::run_jags_model() function.
year	Numeric. The year of model estimated you wish to pull.
country	String. The name of the country you wish to inspect.

Value

A dataframe of model estimates for each method, with the median (50%), 80% and 95% credible intervals.

Examples

```
## Not run:
raw_data <- get_data(national=TRUE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2025.5, nsegments=12, raw_data)
mod <- run_jags_model(jagsdata = jagsdata, jagsparams = NULL, n_iter = 5, n_burnin = 1, n_thin = 1)
estimates <- pull_estimates(model_output = mod, year=2018, country="Nepal")

## End(Not run)
```

run_jags_model	<i>Wrapper function to run the jags model for estimating the proportion of modern contraceptive methods supplied by the public & private Sectors using a Bayesian hierarchical penalized spline model for the national and subnational administration levels</i>
----------------	--

Description

Wrapper function to run the jags model for estimating the proportion of modern contraceptive methods supplied by the public & private Sectors using a Bayesian hierarchical penalized spline model for the national and subnational administration levels

Usage

```
run_jags_model(
  jagsdata,
  jagsparams = NULL,
  n_iter = 80000,
  n_burnin = 10000,
  n_thin = 35,
  n_chain = 2,
  n_cores = NULL,
  ...
)
```

Arguments

jagsdata	The object from the mcmsupply::get_modelinputs() function.
jagsparams	The parameters of the JAGS model you wish to review
n_iter	Default is 80000. Number of iterations to do in JAGS model.
n_burnin	Default is 10000. Number of samples to burn-in in JAGS model.
n_thin	Default is 35. Number of samples to thin by in JAGS model.
n_chain	Default is 2. Number of chains to run in your MCMC sample.
n_cores	The number of cores to use for parallel execution in subnational estimation. If not specified, the number of cores is set to the value of options("cores"), if specified, or to approximately half the number of cores detected by the parallel package.
...	Arguments from the mcmsupply::get_modelinputs() function.

Value

returns the jags model object

Examples

```
raw_data <- get_data(national=TRUE, local=TRUE, mycountry="Nepal")
jagsdata <- get_modelinputs(startyear=1990, endyear=2025.5, nsegments=12, raw_data)
run_jags_model(jagsdata, n_iter=5, n_burnin=1, n_thin=1)
```

subnat_FPsource_data	<i>DHS survey observations for the proportion of modern contraceptives supplied by the public and private sectors at the subnational administration level.</i>
----------------------	--

Description

Elizabeth Heger Boyle, Miriam King and Matthew Sobek. IPUMS-Demographic and Health Surveys: Version 9 (dataset). IPUMS and ICF, 2022. <https://doi.org/10.18128/D080.V9>

Usage

```
subnat_FPsource_data
```

Format

subnat_FPsource_data:

A data frame with 6940 rows and 8 columns:

Country Country names

Region Subnational region names

Method Contraceptive method name

average_year Average year of the survey

sector_categories Name of sector

proportion Proportion supplied by the sector

SE.proportion Standard error associated with the proportion

n Sample size associated with the observation

Source

On request from IPUMS - <https://www.idhsdata.org/idhs/index.shtml>

subnat_FPsource_format

A checklist for ensuring subnational-level custom data is appropriate to be used for estimation

Description

A checklist for ensuring subnational-level custom data is appropriate to be used for estimation

Usage

subnat_FPsource_format

Format

A list of requirements for custom data to meet before being accepted into the model

Country Country name variable classification

Region Subnational region name variable classification

Method Method name variable classification

average_year average_year variable classification

sector_categories sector_categories name variable classification

proportion proportion variable classification

SE.proportion SE.proportion variable classification

n n variable classification

subnational_alpha_cms_hat

The median estimates of the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This array is used to inform the Normal prior of the subnational-level intercept in the single-country subnational model.

Description

The median estimates of the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This array is used to inform the Normal prior of the subnational-level intercept in the single-country subnational model.

Usage

subnational_alpha_cms_hat

Format

A array of 23 matrices with 2 rows and 5 columns

subnational_estimated_correlations

The estimated subnational-level correlations between the rates of change in methods

Description

The estimated subnational-level correlations between the rates of change in methods

Usage

subnational_estimated_correlations

Format

A array of 2 matrices with 5 rows and 5 columns:

row Contraceptive method the correlation estimate refers to

column Contraceptive method the correlation estimate refers to

public_cor The estimated correlation between the rates of change in methods supplied by the public sector

private_cor The estimated correlation between the rates of change in methods supplied by the private sector

subnational_inv.sigma_delta_hat

The median estimate for the subnational-level precision matrix of the delta.k terms in the multi-country subnational model. This array is used to inform the multi-variate normal prior in the single-country subnational model.

Description

The median estimate for the subnational-level precision matrix of the delta.k terms in the multi-country subnational model. This array is used to inform the multi-variate normal prior in the single-country subnational model.

Usage

subnational_inv.sigma_delta_hat

Format

A array of 2 matrices with 5 rows and 5 columns:

Array 1 Estimated public sector precision matrix

Array 2 Estimated private sector precision matrix

subnational_tau_alpha_pms_hat

subnational_tau_alpha_pms_hat The median estimates of the precision for the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This vector is used to inform the precision in the Normal prior of the subnational-level intercept in single-country subnational models.

Description

subnational_tau_alpha_pms_hat The median estimates of the precision for the subnational-level country, sector-, method-specific intercepts in the multi-country subnational model. This vector is used to inform the precision in the Normal prior of the subnational-level intercept in single-country subnational models.

Usage

subnational_tau_alpha_pms_hat

Format

A vector of two precision estimates

Index

- * **Country_and_area_classification**
 - Country_and_area_classification, [5](#)
- * **DEFT_DHS_database**
 - DEFT_DHS_database, [6](#)
- * **country_names**
 - country_names, [6](#)
- * **datasets**
 - national_FPsource_data, [11](#)
 - national_FPsource_VARCOV_bivarlogitnormal, [12](#)
 - national_varcov_order_bivarlogitnormal, [15](#)
 - subnat_FPsource_data, [18](#)
- * **national_FPsource_format**
 - national_FPsource_format, [12](#)
- * **national_estimated_correlations_bivarlogitnormal**
 - national_estimated_correlations_bivarlogitnormal, [10](#)
- * **national_inv_sigma_delta_hat_bivarlogitnormal**
 - national_inv_sigma_delta_hat_bivarlogitnormal, [13](#)
- * **national_tau_alpha_cms_hat_bivarlogitnormal**
 - national_tau_alpha_cms_hat_bivarlogitnormal, [14](#)
- * **national_theta_rms_hat_bivarlogitnormal**
 - national_theta_rms_hat_bivarlogitnormal, [14](#)
- * **subnat_FPsource_format**
 - subnat_FPsource_format, [19](#)
- * **subnational_alpha_cms_hat**
 - subnational_alpha_cms_hat, [19](#)
- * **subnational_estimated_correlations**
 - subnational_estimated_correlations, [20](#)
- * **subnational_inv_sigma_delta_hat**
 - subnational_inv.sigma_delta_hat, [20](#)
- * **subnational_tau_alpha_pms_hat**
 - subnational_tau_alpha_pms_hat, [21](#)
- calculate_SE_data_from_DTA, [3](#)
- check_data_freshness, [4](#)
- Country_and_area_classification, [5](#)
- country_names, [6](#)
- DEFT_DHS_database, [6](#)
- get_data, [7](#)
- get_modelinputs
 - (get_subnational_modelinputs), [8](#)
- get_posterior_P_samps, [8](#)
- get_subnational_modelinputs, [8](#)
- national_estimated_correlations_bivarlogitnormal, [10](#)
- national_FPsource_data, [11](#)
- national_FPsource_format, [12](#)
- national_FPsource_VARCOV_bivarlogitnormal, [12](#)
- national_inv_sigma_delta_hat_bivarlogitnormal, [13](#)
- national_tau_alpha_cms_hat_bivarlogitnormal, [14](#)
- national_theta_rms_hat_bivarlogitnormal, [14](#)
- national_varcov_order_bivarlogitnormal, [15](#)
- plot_estimates, [15](#)
- pull_estimates, [16](#)
- run_jags_model, [17](#)
- subnat_FPsource_data, [18](#)

subnat_FPsource_format, [19](#)
subnational_alpha_cms_hat, [19](#)
subnational_estimated_correlations, [20](#)
subnational_inv.sigma_delta_hat, [20](#)
subnational_tau_alpha_pms_hat, [21](#)